

ZYXEL

Zyxel XS1930-12HP-ZZ0101F Netzwerk-Switch Managed L3 10G Ethernet (100/1000/10000) Power over Ethernet (PoE) Schwarz

Marke : Zyxel

Artikel-Code: XS1930-12HP-ZZ0101F

Produktname : XS1930-12HP-ZZ0101F



Zyxel XS1930-12HP-ZZ0101F. Switch-Typ: Managed, Switch-Ebene: L3. Basic Switching RJ-45 Ethernet Ports-Typ: 10G Ethernet (100/1000/10000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 10. MAC-Adressentabelle: 16000 Eintragungen, Routing-/Switching-Kapazität: 240 Gbit/s. Netzstandard: IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3af,.... Power over Ethernet (PoE). Rack-Einbau



Management-Funktionen		Design	
Switch-Typ *	Managed	Produktfarbe	Schwarz
Switch-Ebene	L3	LED-Anzeigen	✓
Quality of Service (QoS) Support	✓	Energie	
Web-basiertes Management	✓	Netzteil enthalten *	✓
Cloud-verwaltet	✓	AC Eingangsspannung	100 - 240 V
Konfiguration der Standorteinstellungen (CLI)	✓	AC Eingangsfrequenz	50 - 60 Hz
MIB Unterstützung	✓	Stromverbrauch (max.)	493 W
Anschlüsse und Schnittstellen		Power over Ethernet (PoE)	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	10	Power over Ethernet (PoE) *	✓
Basic Switching RJ-45 Ethernet Ports-Typ *	10G Ethernet (100/1000/10000)	Anzahl Power over Ethernet plus (PoE+) Anschlüsse	8
Menge Modul-Steckplätze SFP+	2	Gesamtleistung Power over Ethernet (PoE)	375 W
Netzwerk		Betriebsbedingungen	
Netzstandard *	IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3an, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3x	Betriebstemperatur	-20 - 50 °C
		Temperaturbereich bei Lagerung	-40 - 70 °C
10G-Unterstützung *	✓	Relative Luftfeuchtigkeit in Betrieb	5 - 95%
Port-Spiegelung	✓	Luftfeuchtigkeit bei Lagerung	5 - 95%
Ethernet LAN Datentransferraten	100,1000,2500,5000,10000 Mbit/s	Wärmeableitung	151,06 BTU/h
VLAN-Unterstützung	✓	Gewicht und Abmessungen	
Datenübertragung		Breite	330 mm
Routing-/Switching-Kapazität *	240 Gbit/s	Tiefe	230 mm
MAC-Adressentabelle *	16000 Eintragungen	Höhe	44 mm
		Gewicht	2,8 kg
		Logistikdaten	
		Warentarifnummer (HS)	85176990

Multicast-Funktionen

Multicast Unterstützung	✓
-------------------------	---

Design

Rack-Einbau *	✓
---------------	---



4718937605262

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.